















- · Dirt repellent.
- Seams face downwards so sparks can not get lodged in them.
- Durable triple stitched seams that extend the product life.
- Adjustable kneepad pockets so kneepads can be optimally placed on the knee.
- Co-certified for use with MASCOT kneepad type, LONG.

Technical info

Anti-static, acid-protective and flame retardent. Dirt resistant. Protects from electric arcs and occasional welding arcs. Double and triple stitched seams on leg and crotch. Adjustable straps in short, strong elastic with plastic buckles. Large bib pocket with pen opening and flap with hidden press studs. Phone pocket with zip. Adjustable waist. D-ring. Fly with zip. Ergonomically formed trouser leg. Front pockets. Back pockets with reinforcement, flap and hidden press studs. Thigh pocket with flap and hidden press studs. Phone thigh pocket. Reinforced ruler pocket. Adjustable knee pad pockets with flap and top access. Each standard leg length can be lengthened by 3 cm by releasing the internal red stitching. Reflectors. We recommend 00718-100, 50451-916 and 20118-915 kneepads for this model. Co-certified together with kneepad type LONG in accordance with EN 14404.

13669-216 Bib & Brace with kneepad pockets

dirt repellent - multi-protective MASCOT® MULTISAFE



82C42	82C44	82C46	82C48	82C50	82C52	82C54
82C56	82C58	82C60	82C62	82C64	82C66	82C68
90C46	90C48	90C50	90C52	90C54	90C56	90C58
90C60	90C62	76C46	76C48	76C50	76C52	76C54
76C56						

60% modacrylic/39% cotton/1% carbon fibres $275~\text{g/m}^2$











Twill/Ripstop.Shrinkage max. 3%.Flourocarbon impregnation is required after each wash to maintain EN 13034 protection

Industrial care category B1

Certifications

















Logo

Due to the unique properties of the fabric, logo printing is only available through the use of specific transfer types. As this is a safety product, we strongly recommend that MASCOT affix the logo to reduce the risk of errors. Please contact customer service for further information.

Logo placement:

Workwear logo. Special placement. Contact to discuss further

User











