19435-231 Winter Jacket



CLIMASCOT®-lining - breathable - windproof - water-repellent

MASCOT® ACCELERATE SAFE



XS	S	M	L	XL	2XL	3XL
4XL	5XL					




- Breathable, windproof and water-repellent.
- Unique CLIMASCOT® insulation provides warmth without bulk. Lightweight, soft CLIMASCOT® insulation takes up almost no space when compressed.
- The zip fastener has a double storm flap to provide extra protection against bad weather.
- Interior zipper at lower back for logo printing / embroidery.

Technical info

Fluorescent, with oblique transverse reflective strips. Breathable, windproof and water-repellent. CLIMASCOT® Lightweight Insulation. Two-toned. High collar. Fastening with zip and double storm flap. Inner pocket with mesh material. Chest pocket with a zip. D-ring. Front pockets with hidden press stud fastening. Elastic at cuffs. Elastic at the sides and waist. Zip at lower back for logo printing/ embroidery. In order to achieve EN ISO 20471 class 3, the sizes XS and S do not have a contrast colour.

User



Main material/upper material

100% polyester

210 g/m²



Ripstop.Hydrostatic pressure test > 10,000 mmH²O according to EN ISO 811.According to EN ISO 20471, this product is certified to retain its properties with 50 domestic washes.Shrinkage max. 2%.

Industrial care category B3

CLIMASCOT® Lightweight Insulation

Certifications



- OEKO-TEX® STANDARD 100
- EN ISO 20471 - class 3
- EN 342 3/WP (2.12 clo)
- Hi-Vis Group A
- ProWash®

Logo

You should choose a transfer that can be heated to a maximum of 145 degrees when being printed onto the product. Remember to check the washing instructions for the chosen transfer before washing the product.

The product is certified with a maximum logo area of 0,1200m². This approved area must not be exceeded. Logos respectively on the front or back of the product, can only constitute a maximum of 50% of the total approved logo area in order to maintain the EN ISO 20471-certification. Note: The listed area is only a guide to how much space is available for logo placement. In order to maintain the product's hi-vis class according to EN ISO 20471, the instructions on logo size must be observed.

Logo placement:

- Workwear logo stretch. Left breast. Max 8x6 cm/3.1x2.3 inches

- Workwear logo stretch. Over left breast pocket. Max 9x3 cm/3.5x1.1 inches
- Workwear logo stretch. Right breast. Max 10x5 cm/3.9x1.9 inches
- Workwear logo stretch. Mid-back. Max 25x18 cm/9.8x7 inches
- Workwear logo stretch. On the nape. Max 12x3 cm/4.7x1.1 inches
- Workwear logo stretch. Horizontal on right sleeve. Max 10x5 cm/3.9x1.9 inches
- Workwear logo. Special placement. Contact to discuss further