21019-292 Winter Boilersuit

two-toned - flame retardant - ULTIMATE STRETCH

MASCOT® ACCELERATE MULTISAFE



17010

S	M	L	XL	2XL	3XL	4XL
5XL						

ERGONOMIC FIT | KNEE PAD POCKET | CLICK POCKET SYSTEM | ULTIMATE STRETCH

- A high level of protection with anti-static, acid protection and flame retardant properties.
- Protects from electric arcs.
- Windproof and waterproof with taped seams.
- Stretch material provides optimal freedom of movement.
- Padded lining keeps you warm.
- CORDURA® reinforcements on the front of the leg.

Technical info

Two-toned. Fluorescent, with oblique transverse reflective strips. ULTIMATE STRETCH. Anti-static, acid-protective and flame retardent. Protects from electric arcs. Prepared for holster pockets, attachable with the Click Pocket System. Padded lining. High collar. Fastening with zip and double storm flap. Chest pocket with a zip. Prepared for attachment of ID card. Double stitched seams on the leg and crotch. Ergonomically formed trouser leg. Front pockets. Back pockets with flap. Reinforced ruler pocket with flap. Thigh pocket with phone pocket and flap with hidden press studs. Adjustable kneepad pockets with CORDURA fabric. Elastic at the waist. With print effects. The product has a surface treatment that is repellent and resistant to the permeation of sulfuric acid and sodium hydroxide in accordance with EN 13034 Type 6. Supplement the product with a hood, 21410-292 or 21510-292 (see MASCOT® COMPLETE). Co-certified together with kneepad type large in accordance with EN 14404-3.

User

♂ ♀

Main material/upper material

36% modacrylic/25% cotton/18% polyamide/9% polyurethane/6% elastolefin/5% aramid/1% carbon fibres

335 g/m²

60

ULTIMATE STRETCH.Ripstop.Shrinkage max. 3%.According to EN ISO 20471, this product is certified to retain its properties with 25 domestic washes.Impregnation is required after each wash to maintain EN 13034 protection.

Industrial care category B3

CORDURA FABRIC

Certifications

OEKO-TEX® STANDARD 100 | EN 1149-5 | EN ISO 11612 | EN 13034 | EN 342 3/WP | EN ISO 24232 4-1-X | EN 61482-1-2 | EN IEC 61482-1-1 | EN ISO 20471 3 | HIGH-VIS GROUP: Y

- OEKO-TEX® STANDARD 100
- EN 1149-5 (tested according to EN 1149-3)
- EN ISO 11612 (A1, B1, C1, E2, F1)
- EN 13034 (Type 6)
- EN 342 3/WP (2.39 clo)
- EN ISO 24232 4-1-X
- EN 61482-1-2 APC 2
- EN IEC 61482-1-1 (ELIM 36 cal/cm², ATPV 37 cal/cm²)
- EN ISO 20471 - class 3
- Hi-Vis Group Y

Logo

Due to the unique properties of the fabric, logo printing is only available through the use of specific transfer types. As this is a safety product, we strongly recommend that MASCOT affix the logo to reduce the risk of errors. Please contact customer service for further information.

The product is certified with a maximum logo area of 0,8300m². This approved area must not be exceeded. Logos

respectively on the front or back of the product, can only constitute a maximum of 50% of the total approved logo area in order to maintain the EN ISO 20471-certification. Note: The listed area is only a guide to how much space is available for logo placement. In order to maintain the product’s hi-vis class according to EN ISO 20471, the instructions on logo size must be observed.