



## 24401-231 Outer Shell Jacket

breathable - wind- and waterproof

MASCOT® ACCELERATE SAFE

14

XS	S	M	L	XL	2XL	3XL
4XL	5XL					

### Main material/upper material

100% polyester

210 g/m<sup>2</sup>



- Breathable, wind and waterproof with taped seams.
- Detachable lined hood with adjustable elastic drawstring.
- The zip fastener has a double storm flap to provide extra protection against bad weather.
- Flap on back of jacket can be folded up for standard back length or released for extended back.



Ripstop. Hydrostatic pressure test > 10,000 mmH<sub>2</sub>O according to EN ISO 811. According to EN ISO 20471, this product is certified to retain its properties with 50 domestic washes. Shrinkage max. 2%.

### Industrial care category B3

### Technical info

Fluorescent and with vertical and oblique, transverse reflective strips. The fabric is highly durable, breathable, wind and waterproof. Taped seams. Detachable lined hood with adjustable drawstring. Fastening with zip and double storm flap. Inner pockets - two with zips and one open mesh. Detachable ID card holder. Chest pocket with a zip. Front pockets with a zip. High collar. Rib inside the bottom trim on the front of the jacket. Flap on back of jacket can be folded up for standard back length or released for extended back. Rib (hidden in storm flap) at cuffs. Hook and loop band fastening at cuffs.

### User



### Certifications



- OEKO-TEX® STANDARD 100
- EN ISO 20471 - class 3
- Hi-Vis Group A
- EN 343 4-4-X
- RIS-3279-TOM, ONLY colour 14
- ProWash®

### Logo

You should choose a transfer that can be heated to a maximum of 145 degrees when being printed onto the product. Remember to check the washing instructions for the chosen transfer before washing the product.

The product is certified with a maximum logo area of 0,1264m<sup>2</sup>. This approved area must not be exceeded. Logos respectively on the front or back of the product, can only constitute a maximum of 50% of the total approved logo area in order to maintain the EN ISO 20471-certification. Note: The listed area is only a guide to how much space is available for logo placement. In order to maintain the product's hi-vis class according to EN ISO 20471, the instructions on logo size must be observed.

### Logo placement:

- Workwear logo. Over left breast pocket. Max 8x3 cm/3.1x1.1 inches
- Workwear logo. Left breast pocket. Max 8x7 cm/3.1x2.7 inches

- Workwear logo stretch. Right breast. Max 8x6 cm/3.1x2.3 inches
- Workwear logo. Over right breast pocket. Max 8x3 cm/3.1x1.1 inches
- Workwear logo stretch. Mid-back. Max 20x20 cm/7.8x7.8 inches
- Workwear logo. Horizontal on right sleeve. Max 10x5 cm/3.9x1.9 inches
- Workwear logo. Horizontal on left sleeve. Max 10x5 cm/3.9x1.9 inches
- Workwear logo. Special placement. Contact to discuss further