

25078-442 Trousers with kneepad pockets

Ladies fit DIAMOND - Stretch Zones - CORDURA®

MASCOT® ACCELERATE

010

82C34	82C36	82C38	82C40	82C42	82C44	82C46
82C48	82C50	82C52	82C54	82C56	76C34	76C36
76C38	76C40	76C42	76C44	76C46	76C48	76C50
76C52	76C54	76C56				

DIAMOND FIT | STRETCH ZONES | LIGHTWEIGHT | ERGONOMIC FIT | KNEE PAD POCKET | REFLECTORS

- Stretch zones provide greater freedom of movement.
- Holster pockets can be easily added with the Click Pocket System.
- Thigh pocket with phone pocket and concealed metal press stud under flap.
- Zippers and buttons are made of metal so that they are traceable.
- The kneepad pockets of durable CORDURA® are adjustable so the kneepads have the optimal position on your knees.

Technical info

Ladies fit DIAMOND. Designed with food industry technicians in mind. Focus on traceability and reduced risk of lost items. Detectable metal buttons and zippers. Stretch fabric on parts of the product. Combination of the lightweight fabric quality 442 and ULTIMATE STRETCH in fabric quality 511. Prepared for holster pockets, attachable with the Click Pocket System. Double and triple stitched seams on the leg and crotch. Low waist and form cut waist band. Ergonomically formed trouser leg. Belt loops. Fly with zip. Front pockets. Back pockets. Thigh pocket with phone pocket and flap with concealed metal press stud. CORDURA® fabric reinforced ruler pocket with small internal pocket. Kneepad pockets made from durable CORDURA® (1000 D). Simple individual adjustment of kneepad pocket height. With print and reflectors. Each standard leg length can be lengthened by 3 cm by releasing the internal red stitching. Co-certified together with kneepad type large in accordance with EN 14404-3.

User

Main material/upper material

65% polyester/35% cotton

270 g/m²

60

Twill.

Industrial care category A1

CORDURA FABRIC

Certifications

OEKO-TEX® STANDARD 100 | ProWash® EN ISO 15797

- OEKO-TEX® STANDARD 100
- ProWash® - EN ISO 15797

Logo

You should choose a transfer that can be heated to a maximum of 145 degrees when being printed onto the product. Remember to check the washing instructions for the chosen transfer before washing the product.

