25249-236 ¾ Length Trousers with kneepad pockets

Stretch Zones - ProWash®

MASCOT® ACCELERATE SAFE

14 17 222

C44	C45	C46	C47	C48	C49	C50
C51	C52	C54	C56	C58	C60	C62
C64	C66	C68				



STRETCH ZONES | LIGHTWEIGHT | ERGONOMIC FIT | KNEE PAD POCKET

- Light and strong fabric with ripstop. Ripstop is a super durable weave that helps fabric to last for a very long time.
- The product is a combination of regular fabric and stretch fabric, with the stretch fabric placed where extra freedom of movement is required.
- Add your favourite holster pockets using the Click Pocket System.
- Ergonomically shaped trouser legs are constructed to follow the body's natural movements.
- Adjustable kneepad pockets so kneepads can be optimally placed on the knee.
- The product tolerates industrial washing.

Technical info

Fluorescent with reflective tape. Stretch fabric on parts of the product. Combination of the lightweight fabric quality 236 and ULTIMATE STRETCH in fabric quality 511. Prepared for holster pockets, attachable with the Click Pocket System. Double stitched seams on the leg and crotch. Hidden stud fastening. Ergonomically formed trouser leg. Belt loops. D-ring. Fly with zip. Front pockets. Back pockets with reinforcement. Hidden tool strap on right side. Reinforced ruler pocket. Thigh pockets with flaps. Adjustable kneepad pockets. Simple individual adjustment of kneepad pocket height. Thigh pocket with phone pocket and flap with hidden press studs. Co-certified together with kneepad type large in accordance with EN 14404-3.

User

Main material/upper material

70% polyester/30% cotton

215 g/m²

Twill/Ripstop.Shrinkage max. 2%.The product is certified to retain its properties with 50 domestic washes or 40 industrial washes.Wash separately.Do not use fabric softner.

Industrial care category B1

Certifications

OEKO-TEX® STANDARD 100 | EN ISO20471 2 | HIGH-VIS GROUP: X | ProWash® | RIS-3279-TOM

- OEKO-TEX® STANDARD 100
- EN ISO 20471 - class 2
- Hi-Vis Group X
- ProWash®
- RIS-3279-TOM, ONLY colour 14

Logo

The product is certified with a maximum logo area of 0,1300m². This approved area must not be exceeded. Logos respectively on the front or back of the product, can only constitute a maximum of 50% of the total approved logo area in order to maintain the EN ISO 20471-certification. Note: The listed area is only a guide to how much space is available for logo placement. In order to maintain the product's hi-vis class according to EN ISO 20471, the instructions on logo size must be observed.