

## F1006-906 Safety Shoe

S3S - laces

MASCOT® FOOTWEAR CLASSIC



09

|      |      |      |      |      |      |      |
|------|------|------|------|------|------|------|
| 0836 | 0837 | 0838 | 0839 | 0840 | 1040 | 1041 |
| 1042 | 1043 | 1044 | 1045 | 1046 | 1047 | 1048 |
| 1049 | 1050 | 1051 | 1052 |      |      |      |

### Main material/upper material

Microfibre

Size 42: 615 g

|                                 |                          |                                              |                                              |                             |                                          |
|---------------------------------|--------------------------|----------------------------------------------|----------------------------------------------|-----------------------------|------------------------------------------|
| <b>E</b><br>Shock-absorbing     | <b>A</b><br>Antistatic   | <b>PS</b><br>Textile nail protection (Ø=3mm) | <b>WPA</b><br>Water repellent and breathable | <b>SR</b><br>Slip resistant | <b>FO</b><br>Oil and fuel resistant sole |
| <b>SC</b><br>Scuff cap abrasion | <b>LG</b><br>Ladder grip |                                              |                                              |                             |                                          |

- Water-repellent and durable upper in a tightly woven microfibre.
- Composite toe cap and PU-reinforced scuff cap ensure the necessary protection and make the shoes extra durable.
- A ladder grip beneath the sole ensures optimum grip on the rungs of the ladder and helps prevent slips.
- Very durable, slip-resistant PU outer sole that's heat-resistant up to 140°C.

### Technical info

Metal free. Water-repellent. Lace fastening. Toe reinforcement with PU. Composite toe cap. MASCOLAYER® textile nail protection. Stabilising multi-functional shank with integrated absorbing cushioning. Light moulded scuff cap. Suitable for working on the knees. Shock-absorbing insoles are removable, durable and ergonomic. Heat resistant sole up to 140°C. Profile depth 2.5mm. Heel cap. Sole is oil and petrol resistant. Non-marking sole – no scuff marks. Absorbs and removes moisture. Ladder grip. ESD approved to EN IEC 61340-4-3: 2002 + EN IEC 61340-5-1: 2008.

### User



### Certifications

|            |           |           |           |           |                                                                                       |                                                                                       |
|------------|-----------|-----------|-----------|-----------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>S3S</b> | <b>SR</b> | <b>FO</b> | <b>SC</b> | <b>LG</b> |  |  |
|------------|-----------|-----------|-----------|-----------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|

- Safety Class S3S
- Slip resistant (SR)
- Oil and fuel resistant sole (FO)
- Scuff cap abrasion (SC)
- Ladder grip (LG)
- Electrostatic discharge (ESD)
- EN ISO 20345: 2022