

F1100-902 Safety boot S1PS, asphalt

S1PS - BOA® Fit System

MASCOT® FOOTWEAR INDUSTRY



09

1040	1041	1042	1043	1044	1045	1046
1047	1048	1049	1050			

Main material/upper material

Full grain

Size 42: 750 g

E Shock-absorbing	A Antistatic	PS Textile nail protection (Ø=3mm)	WPA Water repellent and breathable	HRO Heat-resistant outsole compound	SR Slip resistant
HI Heat insulation	FO Oil and fuel resistant sole				

- Thermal insulating asphalt boot that protects your feet from extreme heat.
- Extra protective flap over the BOA® Fit System.
- Rubber outer sole that's heat-resistant up to 300°C contact heat.
- Slip-resistant outer sole without tread pattern.

Technical info

Developed with a focus on asphalt work with a special outsole without tread pattern. Opens and fastens with BOA® Fit System, which consists of a rotational dial, wire and guides. Protective flap covering BOA® Fit System. Composite toe cap. Nail protection of special textile material. Midsole of PU. Insoles are removable. Shock absorbing insole. Heel cap. Sole made of rubber with extreme slip resistance. Heat resistant sole up to 300°C contact heat. Non-marking sole – no scuff marks.

User



Certifications



EN ISO 20345



- Safety Class S1PS
- Heat insulation (HI)
- Heat-resistant outsole compound (HRO)
- Slip resistant (SR)
- Oil and fuel resistant sole (FO)
- Water repellent and breathable (WPA)
- Electrostatic discharge (ESD)
- EN ISO 20345: 2022